



ATTIC COVERAGE CHART – BLOW-IN CELLULOSE INSULATION

DO NOT ADD WATER TO THIS PRODUCT

		19.05 lbs. (8.64 kg)				INS541LD	
R-Value at 75° F Mean Temp. Valor de resistencia térmica (valor R) a 75 °F de temperatura media	Minimum Thickness (inches) Espesor mínimo (en pulgadas)		Net Coverage (no adjustment for framing) Cobertura neta (sin compensación para la estructura)			Net Coverage (adjusted for 2" x 6" framing on 16" centers) Cobertura neta (con compensación para una estructura de 2" x 6" en centros de 16")	
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Pies cuadrados máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. Peso mínimo por pie cuadrado	Maximum Sq. Ft. per Bag Pies cuadrados máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados
13	4.29	3.86	56.0	17.9	0.340	61.8	16.2
19	6.19	5.57	36.7	27.2	0.519	40.0	25.0
22	7.12	6.41	31.1	32.2	0.613	33.5	29.8
25	8.05	7.25	26.8	37.2	0.710	28.7	34.9
30	9.57	8.62	21.7	46.1	0.878	22.9	43.6
38	11.97	10.77	16.4	61.1	1.164	17.1	58.5
49	15.20	13.68	12.0	83.5	1.591	12.4	80.7
60	18.37	16.53	9.3	108.1	2.059	9.5	105.0

BLOW-IN CELLULOSE APPLICATIONS

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 19.05 LBS USING THE GREENFIBER MONARCH BLOWING MACHINE. SETTINGS ARE NOT ADJUSTABLE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM INSTALLED THICKNESS TO ENSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF DESIRED R-VALUE. THIS PRODUCT MUST BE INSTALLED DRY. THIS COVERAGE CHART DOES NOT APPLY TO FLOOR APPLICATIONS. DO NOT ADD WATER TO THIS PRODUCT. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. MINIMUM NET WEIGHT IS 18.1 LBS.

SIDEWALL COVERAGE CHART DRY DENSE-PACK APPLICATION

DO NOT ADD WATER TO THIS PRODUCT		19.05 lbs. (8.64 kg)		INS541LD		
Thermal Resistance (R value) Resistencia térmica (R)	Framing Estructura	Installed Thickness (inches) Espesor instalado (pulgadas)	Minimum Wt. Per Square Foot lb/ft ² Peso mínimo por pie cuadrado lb/ft ²	Maximum Coverage Per Bag (No Adjustment for Framing) ft ² /Bag Cobertura máxima por bolsa (sin compensación para la estructura) ft ² /Bag	Maximum Coverage Per Bag (Adjusted for Framing) ft ² /Bag Cobertura máxima por bolsa (con compensación para la estructura) ft ² /Bag	
					(16" oc)	(24" oc)
13	2x4	3.5	1.02	18.7	20.6	19.9
21	2x6	5.5	1.60	11.9	13.1	12.7

THIS COVERAGE CHART IS FOR DRY APPLICATIONS ONLY AND IS BASED ON THE KRENLD KS200, WITH MATERIAL APPLIED DRY. FOR MAXIMUM COVERAGE PER BAG (ADJUSTED FOR FRAMING), THE FRAMING FACTOR FOR 16" OC STUD SPACING IS 9.375%; FOR 24" OC STUD SPACING THE FRAMING FACTOR IS 6.25%.

Greenfiber® provides outstanding thermal performance, fire-resistance and sound control. Consisting of up to 85% recycled content, Greenfiber® Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

CERTIFICATION

This insulation has been installed in conformance with the above recommendations, to provide a value of R-_____ using _____ bags of this insulation to cover _____ square feet of area.

Builder's Signature _____

Company Name _____

Date _____

Applicator's Signature _____

Company Name _____

Date _____

Manufactured by
US Greenfiber, LLC

Toll-Free 800-228-0024
www.greenfiber.com

Greenfiber is a registered trademark of US Greenfiber, LLC.
All rights reserved.
© 2020 US Greenfiber, LLC.
All rights reserved.

US Greenfiber, LLC
5500 77 Center Drive, Suite 100
Charlotte, NC 28217

Mesa, AZ 85212
Norfolk, NE 68701
Salt Lake City, UT 84119
Tampa, FL 33605
Waco, TX 76704
Wilkes-Barre, PA 18702
Debert, Nova Scotia

Made in USA

