

ATTIC COVERAGE CHART – LOOSE-FILL FORMULA INSULATION

		30 lbs. (13.6 kg)				INS515LD	
R-Value at 75° F Mean Temp. Valor de resistencia térmica (valor R) a 75 °F de temperatura media	Minimum Thickness (inches) Espesor mínimo (en pulgadas)		Net Coverage (no adjustment for framing) Cobertura neta (sin compensación para la estructura)			Net Coverage (adjusted for 2" x 6" framing on 16" centers) Cobertura neta (con compensación para una estructura de 2" x 6" en centros de 16")	
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Pies cuadrados máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. Peso mínimo por pie cuadrado	Maximum Sq. Ft. per Bag Pies cuadrados máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados
11	3.38	3.04	102.5	9.8	0.293	113.1	8.8
13	4.01	3.61	84.9	11.8	0.353	93.7	10.7
19	5.88	5.29	55.2	18.1	0.544	60.5	16.5
22	6.80	6.12	46.6	21.5	0.644	50.4	19.8
26	8.02	7.22	38.4	26.1	0.782	41.0	24.4
30	9.22	8.30	32.4	30.8	0.925	34.3	29.1
32	9.82	8.84	30.0	33.3	0.999	31.7	31.5
38	11.60	10.44	24.4	40.9	1.23	25.6	39.1
40	12.19	10.97	22.9	43.6	1.31	24.0	41.7
44	13.36	12.03	20.4	49.0	1.47	21.2	47.1
48	14.53	13.07	18.3	54.6	1.64	19.0	52.6
49	14.82	13.34	17.9	56.0	1.68	18.5	54.1
50	15.11	13.60	17.4	57.4	1.72	18.0	55.5
60	17.99	16.19	13.8	72.4	2.17	14.2	70.4

LOOSE-FILL APPLICATIONS

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS USING A VOLUMATIC III, 3rd GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. ACTUAL COVERAGE MAY VARY BASED ON CONDITIONS AND IS NOT GUARANTEED BY THE MANUFACTURER. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE ACHIEVEMENT OF THE SPECIFIED R-VALUE. THIS PRODUCT IS INTENDED FOR DRY APPLICATION ONLY. DO NOT ADD WATER TO THIS PRODUCT. MINIMUM NET WEIGHT IS 28.5 LBS.

SIDEWALL COVERAGE CHART DRY DENSE-PACK APPLICATION

(3.5 pcf minimum installed density)		30 lbs. (13.6 kg)			INS515LD	
Thermal Resistance (R value) Resistencia térmica (R)	Framing Estructura	Installed Thickness (inches) Espesor instalado (pulgadas)	Minimum Wt. Per Square Foot lb/ft ² Peso mínimo por pie cuadrado lb/ft ²	Maximum Coverage Per Bag (No Adjustment for Framing) ft ² /Bag Cobertura máxima por bolsa (sin compensación para la estructura) ft ² /Bag	Maximum Coverage Per Bag (Adjusted for Framing) ft ² /Bag Cobertura máxima por bolsa (con compensación para la estructura) ft ² /Bag	
					(16" oc)	(24" oc)
13	2x4	3.5	1.02	29.39	32.4	31.3
21	2x6	5.5	1.60	18.70	20.6	19.9

THIS COVERAGE CHART IS FOR DRY APPLICATIONS ONLY AND IS BASED ON THE KRENLD KS200, WITH MATERIAL APPLIED DRY. FOR MAXIMUM COVERAGE PER BAG (ADJUSTED FOR FRAMING), THE FRAMING FACTOR FOR 16" OC STUD SPACING IS 9.375%; FOR 24" OC STUD SPACING THE FRAMING FACTOR IS 6.25%.

READ THIS BEFORE YOU BUY WHAT YOU SHOULD KNOW ABOUT R-VALUES

This chart shows the R-Value of this insulation. R means resistance to heat flow. The higher the R-Value, the greater the insulating power. Compare insulation R-Values before you buy. There are other factors to consider. The amount of the insulation you need depends on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-Value, it is essential that this insulation be installed properly.

Manufactured by
US Greenfiber, LLC
 Toll-Free 800-228-0024
www.greenfiber.com
 Greenfiber is a registered trademark of US Greenfiber, LLC.
 © 2020 US Greenfiber, LLC.
 All rights reserved.
 US Greenfiber, LLC
 5500 77 Center Drive, Suite 100
 Charlotte, NC 28217
Made in USA

Mesa, AZ 85212
 Norfolk, NE 68701
 Salt Lake City, UT 84119
 Tampa, FL 33605
 Waco, TX 76704
 Wilkes-Barre, PA 18702
 Debert, Nova Scotia

