

## Insulation Fact Sheet

SupremePlus Loose-fill Cellulose Insulation has been installed with the manufacturer's recommendations to provide a value of R-\_\_\_\_\_ using \_\_\_\_\_ bags of insulation to cover \_\_\_\_\_ square feet of area at a thickness of \_\_\_\_\_ inches.

Building Address \_\_\_\_\_

City, State, Zip \_\_\_\_\_

Signature of Installer \_\_\_\_\_

Company Name \_\_\_\_\_

Company City, State, ZIP \_\_\_\_\_

Date Installed \_\_\_\_\_

### THIS IS SUPREMEPLUS LOOSE-FILL CELLULOSE INSULATION

R-value @ 75° F	Initial Installed Thickness (Inches)	Minimum Settled Thickness (Inches)	Number of Bags per 1,000 Square Feet	Maximum Net Coverage Area (Square Feet per Bag)	Number of Bags per 1,000 Square Feet	Maximum Net Coverage Area (Square Feet per Bag)	Minimum Weight per Square Foot (lb/ft <sup>2</sup> )
			<b>Joists 2x6 on 16</b>		<b>No Joists</b>		<b>No Joists</b>
13	4.3	3.8	13.8	72.3	15.3	65.6	0.38
19	5.9	5.3	21.8	45.8	24.1	41.5	0.60
20	6.2	5.6	23.2	43.0	25.6	39.1	0.64
22	6.8	6.1	26.2	38.2	28.6	34.9	0.72
25	7.7	6.9	30.7	32.6	33.2	30.1	0.83
30	9.1	8.2	38.3	26.1	40.9	24.5	1.02
32	9.7	8.7	41.3	24.2	43.9	22.8	1.10
38	11.4	10.3	50.6	19.8	53.2	18.8	1.33
40	12.0	10.8	53.6	18.6	56.3	17.8	1.41
49	14.7	13.2	67.5	14.8	70.3	14.2	1.76
50	15.0	13.5	69.1	14.5	71.8	13.9	1.80
55	16.4	14.8	76.8	13.0	79.6	12.6	1.99
60	17.9	16.1	84.6	11.8	87.4	11.4	2.19

Minimum installed thickness determined according to ASTM C1374 using a Krendl 500 with gate at 7 and air at 6.5. Settings are not adjustable

### GREENFIBER MANUFACTURING LOCATIONS

Chambersburg, PA 17201  
Chandler, AZ 85225

Decatur, AL 35601  
Eastanollee, GA 30538

Hickory, KY 42051  
Lester Prairie, MN 55354  
Webberville, MI 48892

### READ THIS BEFORE YOU BUY

#### What You Should Know About R-values

The chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, your fuel use patterns and family size, proper installation of your insulation, and how tightly your house is sealed against air leaks. If you buy too much insulation, it will cost you more than what you'll save on fuel.

To get the marked R-value, it is essential that this insulation be installed properly.

Chart based on settled thickness, a nominal bag weight of 25 lbs and coverage based on the Krendl 500 blowing machine. Machine settings are not adjustable. Stated R-value is provided by installing the required number of bags per 1,000 sq ft at a minimum installed thickness. Installation of the required number of bags may yield more than the specified minimum thickness and minimum weight per sq ft. Actual coverage will be influenced by job conditions and application techniques and may vary as much as 10% without significantly affecting the stated R-value. Failure of the installer to provide at least the required number of bags per 1,000 sq ft and at least the minimum thickness may result in a lower installed R-value. Compaction may occur during installations above R-30, requiring more than the stated number of bags to obtain the minimum installed thickness. This product is intended for dry loose-fill attic application. This coverage chart does not apply to spray-applied application. Do not add water to this product in attic applications.

Made in USA

Toll-Free 800-228-0024  
www.greenfiber.com

Greenfiber®  
5500 77 Center Drive, Suite 100  
Charlotte, NC 28217  
PM-6.3-330 Rev A 09/23